

THE CLAIMS

1. (Currently Amended) A beverage dispensing device for extracting a substance for preparing a beverage, comprising:

first and second support members pivotally connected together at a support pivot axis and comprising an open position for receiving the substance between the support members and a closed position in which the support members cooperatively define an extraction cavity therebetween, the support members having a front side disposed toward the extraction cavity from the support pivot axis;

a liquid intake associated with the extraction cavity for feeding a liquid into the cavity for mixing with the substance to form a beverage mixture;

a fluid exit associated with the extraction cavity for extracting the mixture; and

a linkage operatively associated with the support members for moving the members relative to each other between the open and closed positions, the linkage comprising:

an operation lever pivotally connected to the second support member at a lever pivot axis, and

a traction arm pivotally connected to the first support member at a traction pivot axis, the traction arm being connected to the operation lever at a connection pivot axis for controlling opening and closing movement of the support members between the open and closed positions upon movement of the operation lever;

wherein the lever and traction pivot axes are disposed in the front side of the support pivot axis with the support members in the closed position

~~wherein the lever is disposed on the same side of the support pivot as the extraction cavity such that both are accessible to a user from the same side.~~

2. (Currently amended) The device of claim 1, wherein the ~~extraction cavity is~~ support members are configured for receiving a package containing the substance in the extraction cavity and for opening the package therein for introducing the liquid and extracting the mixture ~~therefrom~~ from the package.

3. (Original) The device of claim 1, wherein the linkage is configured and the pivot axes disposed such that the traction, lever, and connection pivots axes are aligned with each other at an aligned position during the opening and closing movement.

4. (Original) The device of claim 3, wherein with the support members in the closed position, the connection pivot axis is disposed further from the support pivot axis than a plane defined between the traction and lever pivot axes.

5. (Original) The device of claim 1, wherein the lever comprises a handle disposed at an angle about the lever pivot axis from the connection pivot axis.

6. (Original) The device of claim 1, wherein the connection pivot axis is movable towards and away from the support pivot axis.

7. (Currently amended) ~~The~~ A beverage dispensing device of claim 1 for extracting a substance for preparing a beverage, wherein comprising:

first and second support members pivotally connected together at a support pivot axis and comprising an open position for receiving the substance between the support members and a closed position in which the support members cooperatively define an extraction cavity therebetween, wherein the support members have a front oriented in a direction extending from the support pivot axis toward the extraction cavity, and a rear oriented in an opposite direction from the front;

a liquid intake associated with the extraction cavity for feeding a liquid into the cavity for mixing with the substance to form a beverage mixture;

a fluid exit associated with the extraction cavity for extracting the mixture; and

a linkage operatively associated with the support members for moving the members relative to each other between the open and closed positions, the linkage comprising:

an operation lever pivotally connected to the second support member at a lever pivot axis, the operation lever comprises comprising a handle configured for operation and manipulation by a user for opening and closing the support members, the handle being disposed in front of the extraction cavity with the support members in the closed position, and

a traction arm pivotally connected to the first support member at a traction pivot axis, the traction arm being connected to the operation lever at a connection pivot axis for controlling opening and closing movement of the support members between the open and closed positions upon movement of the operation lever;

wherein the lever is disposed on the same side of the support pivot as the extraction cavity such that both are accessible to a user from the same side.

8. (Original) The device of claim 7, wherein the handle is disposed above the extraction cavity in with the support members in the open position.

9. (Original) The device of claim 8, wherein the linkage is configured such that the handle rotates around the extraction cavity during movement of the support members between the open and closed positions.

10. (Original) The device of claim 7, wherein the handle is disposed in a plane extending between the extraction cavity and the support pivot with the support members in the open position.

11. (Original) The device of claim 7, wherein the extraction cavity has a center, and the traction and lever pivot axes are disposed behind the center of the extraction cavity.

12. (Original) The device of claim 1, wherein at least one of the support members comprises:

a linkage portion that is connected to the linkage,
a cavity portion defining part of the cavity in the closed position, and
a spherical joint rotationally connecting the cavity portion to the linkage portion for enabling the cavity portion to rotate for receiving the substance and aligning against the other of the support members in the closed position.

13. (Original) The device of claim 1, wherein one of the support members is fixed against rotation.

14. (Original) The device of claim 1, wherein the fluid exit is disposed for extracting the mixture from below the extraction cavity.

15. (Original) The device of claim 1, further comprising a heater upstream of the liquid intake and configured for heating the liquid, wherein the liquid comprises water.

16. (Original) The device of claim 1, wherein:

the lever comprises first and second levers pivotally connected to the second support portion at the lever pivot axis; and

the traction arm comprises first and second traction arms pivotally connected to the first support member at a traction pivot axis and to the first and second levers, respectively, at the traction pivot axis.

17. (Original) The device of claim 1, wherein the device is configured for making individual cups of coffee.

18. (Original) The device of claim 1, wherein:

the extraction cavity is configured for receiving a capsule containing the substance;

the liquid intake is configured for injecting the liquid into the capsule in the extraction cavity; and

the fluid exit is configured for opening the capsule for extracting the beverage mixture.

19. (Original) A beverage dispensing device for extracting a substance for preparing a beverage, comprising:

first and second members movably associated with each other for moving between a open and closed positions;

a cavity portion cooperating with the first support member to define an extraction cavity therebetween with the support members in the closed position, the cavity being configured for receiving the substance with the support members in the open position;

a spherical joint rotationally connecting the cavity portion to second support member for enabling the cavity portion to rotate for receiving the substance and aligning against the other of the support members in the closed position;

a liquid intake associated with the extraction cavity for feeding a liquid into the cavity for mixing with the substance to form a beverage mixture; and

a fluid exit associated with the extraction cavity for extracting the mixture.

20. (Original) The device of claim 19, wherein:
the extraction cavity is configured for receiving a capsule containing the substance;
the liquid intake is configured for injecting the liquid into the capsule in the extraction cavity; and
the fluid exit is configured for opening the capsule for extracting the beverage mixture.

21. (New) The device of claim 1, wherein the extraction cavity has a center, and the traction pivot axis is disposed substantially between support pivot axis and the extraction cavity center.

22. (New) The device of claim 1, wherein the lever and connection axes are disposed in the front side with the support members in the closed position.

23. (New) A beverage dispensing device for extracting a substance for preparing a beverage, comprising:

first and second support members pivotally connected together at a support pivot axis and comprising an open position for receiving the substance between the support members and a closed position in which the support members cooperatively define an extraction cavity therebetween;

a liquid intake associated with the extraction cavity for feeding a liquid into the cavity for mixing with the substance to form a beverage mixture;

a fluid exit associated with the extraction cavity for extracting the mixture; and

a linkage operatively associated with the support members for moving the members relative to each other between the open and closed positions, the linkage comprising:

an operation lever pivotally connected to the second support member at a lever pivot axis, and

a traction arm pivotally connected to the first support member at a traction pivot axis, the traction arm being connected to the operation lever at a connection pivot axis for controlling opening and closing movement of the support members between the open and closed positions upon movement of the operation lever,

wherein the linkage is configured and the pivot axes disposed such that the traction, lever, and connection pivots axes are aligned with each other at an aligned position during the opening and closing movement.

24. (New) The device of claim 23, wherein the lever is disposed on the same side of the support pivot as the extraction cavity such that both are accessible to a user from the same side.